


SIDE A




# Coliseum



## R 200 x 75 (80) - 24 x t

TYPE | LW | SW NOMINAL | SW ACTUAL | w | t



Type - LW x SW (SW actual) - w x t (mm)	Mild steel (kg/m <sup>2</sup> )	Aluminium (kg/m <sup>2</sup> )	Available sheet size (mm)	Sheet thickness (mm) measured at the centre	% front open area
R 200 x 75 (80) - 24 x <b>1,5</b>	7,10	2,40	LW 1000 x SW 2000	32 (-) ◆	52,3 (-)
R 200 x 75 (80) - 24 x <b>2,0</b>	9,40	3,20	LW 1250 x SW 2500		
R 200 x 75 (80) - 24 x <b>3,0</b>	14,10	4,70	LW 1500 x SW 3000		
			LW 2000 - 2500 x SW 2500 Max		

◆ Framing profiles: see page 192

SIDE B



# Coliseum

**R 200 x 75 (80) - 24 x t**

| TYPE | LW | | SW NOMINAL | SW ACTUAL | w | t



Type - LW x SW (SW actual) - w x t (mm)	Mild steel (kg/m <sup>2</sup> )	Aluminium (kg/m <sup>2</sup> )	Available sheet size (mm)	Sheet thickness (mm) measured at the centre	% front open area
R 200 x 75 (80) - 24 x <b>1,5</b>	7,10	2,40	LW 1000 x SW 2000	32 (-) ◆	52,3 (-)
R 200 x 75 (80) - 24 x <b>2,0</b>	9,40	3,20	LW 1250 x SW 2500		
R 200 x 75 (80) - 24 x <b>3,0</b>	14,10	4,70	LW 1500 x SW 3000		
			LW 2000 - 2500 x SW 2500 Max		

◆ Framing profiles: see page 192